



Matrix Floodlight 2801P/WD50.MB

Floodlights - Wallwasher DALI with Lens L. 586

Rev. 04/11/2024



Adjustable linear luminaire, suitable for wall, ceiling or ground installation as a stand-alone floodlight. Equipped with secondary optics for different types of light distribution, this version of the Matrix line is particularly suited for the oblique illumination of building façades, to highlight their texture or accentuate the architectural details of historical buildings. RGBW also available.



PHOTOMETRICAL DATA



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Wall, ceiling and stand installation

PROTECTION

IP 67 - IK 07

BODY

Extruded aluminium

SCREEN

Tempered extra-clear glass 5mm with silk-screen priting

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

SIZES

H 100 x L 586 x W 45

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

220-240Vac 50/60Hz






DRIVER Built-in	SOURCE FLUX 2905 lm	CCT LED 3000K
DRIVER CURRENT 500mA	FIXTURE SOURCE 2440 lm	CRI 80
CONTROL DALI-2 integrated	APPARENT EFFICIENCY 84 %	STEP MACADAM 3
SPECIFIC WIRING Inclusa/Included	INSULATION CLASS I	LIFE TIME TM-21 L80B10 80000h Ta 25°C
POWER MODULE LED 24W	OVERVOLTAGE PROTECTION 2kV-4kV	PHOTOBIOLOGICAL RISK RG1
ABSORBED POWER 26W	OPERATING TA 50 °	BEAM OPENING Adjustable Floodlight Flood/28°
SOURCE LED	ENERGETIC CLASS A	

COLORS

							
00 PURE WHITE RAL 9016	01 BLACK RAL 9005	10 WHITE RAL 9010	24 BRONZE	25 RUST	30 ANTHRACIT E	35 SLATE GREY	40 GREY RAL 9006

AcquaStop System Integrated. AcquaStop is a special process inside the product which, through different phases of resination, creates a real barrier, sealing the fixture in a definitive way and preventing the development of condensation inside it.

ACCESSORIES

	MOR685P/2V Connector IP68 2Ways/5Poles L 115 x Ø 34
	MOR685P/3V Connector Y IP68 3Ways/5Poles L 147 x W 73 x H 33
	MOR685P/3VS Connection Box IP68 3Ways/5Poles L 106 x W 140 x H 38
	MOR685P/4VS Connection Box IP68 4Ways/5Poles L 106 x W 120 x H 38
	E.TRA.580 Ultra compact type 2+3 hard wired surge protector L 37 x W 30 x H 30