

Maxima One 375F1/WR8.X3

Urban Lighting - Pole H. 2000 with anti-glare louvre

Rev. 31/10/2023



Maxima comes in two configurations: the first, suitable for residential installation, has a 370 mm lighting body and offers 4 different heights starting from 570 mm and reaching a maximum of 1600 mm. The second, also suitable for semi-urban and urban installation, has a 610 mm lighting body and heights ranging from 1200 mm to 3000 mm. Consisting of chrome-plated louvre reflectors, in addition to guaranteeing a diffuse emission and limiting glare, it actively participates in designing the luminaire in its shape. It is also available with screened louvres suitable for compliance with the Regulations on Light Pollution. The structure is supplied with a flange made with metal clamps necessary to guarantee its stability. The lamp body, firmly connected to the pole by means of a bayonet coupling, makes it easily removable during normal maintenance operations. Dali dimmable on request with extra charge.



PHOTOMETRICAL DATA



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE Ground installation	SCREEN Transparent Polycarbonate	PAINT / FINISHING Anti-corrosive UV stabilised polyester powder
PROTECTION IP 65 - IK 08	SEALS Closed-cell EPDM rubber	SIZES H 2000 x Ø 140 x Ø base 187
BODY Pole: Extruded aluminium alloy - Body/Base: Die-cast aluminium alloy	SCREWS Stainless steel A2	NET WEIGHT 11,6 Kg

ELECTRICAL SPECIFICATIONS




POWER SUPPLY
220-240Vac 50/60Hz

DRIVER Built-in	SOURCE FLUX 6342 lm	CCT LED 3000K
DRIVER CURRENT 425mA	FIXTURE SOURCE 1201 lm	CRI >80
CONTROL DALI available on request	APPARENT EFFICIENCY 19 %	STEP MACADAM 3
SPECIFIC WIRING Inclusa/Included	INSULATION CLASS I	LIFE TIME TM-21 L80B10 80000h Ta 25°C
POWER MODULE LED 42W	OVERVOLTAGE PROTECTION 2kV-4kV	PHOTOBIOLOGICAL RISK RG1
ABSORBED POWER 44W	OPERATING TA 50 °	BEAM OPENING Shielded anti-pollution louvre 360°
SOURCE LED	ENERGETIC CLASS A	

COLORS

							
00 PURE WHITE RAL 9016	01 BLACK RAL 9005	10 WHITE RAL 9010	24 BRONZE	25 RUST	30 ANTHRACIT E	35 SLATE GREY	40 GREY RAL 9006

ACCESSORIES

	MOR683P/2V Connector IP68 2Way/3Poles L 82 x Ø 28
	MOR685P/3V Connector Y IP68 3Ways/5Poles L 147 x W 73 x H 33
	E.TRA.580 Ultra compact type 2+3 hard wired surge protector L 37 x W 30 x H 30