



Up&Down Maxi Wall 7450W/NC3.NW

Wall - Wall luminaire Double Emission - Built-in driver


Rev. 04/11/2024



Wall luminaire configurable in single and double emission, ideal for grazing lighting of external facades. Up&Down Maxi is equipped with various secondary optics for controlling the light flow, which allow design flexibility through different combinations of direct and indirect emission.



PHOTOMETRICAL DATA



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Wall installation

PROTECTION

IP 66 - IK 08

BODY

Die-cast aluminium

SCREEN

Tempered extra-clear glass 6mm with silk-screen printing

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

SIZES

H 420 x W 234 x Ø 180

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

220-240Vac 50/60Hz


DRIVER

Built-in	SOURCE FLUX 8100 lm	CCT LED 4000K
DRIVER CURRENT 600mA	FIXTURE SOURCE 6400 lm	CRI >80
CONTROL ON/OFF	APPARENT EFFICIENCY 79 %	STEP MACADAM 3
POWER MODULE LED 46W	INSULATION CLASS I	LIFE TIME TM-21 L80B10 80000h Ta 25°C
ABSORBED POWER 48W	OVERVOLTAGE PROTECTION 2kV-4kV	PHOTOBIOLOGICAL RISK RG1
SOURCE LED COB	OPERATING TA 50 °	BEAM OPENING Dual Flood/16°+48°

COLORS

							
00 PURE WHITE RAL 9016	01 BLACK RAL 9005	10 WHITE RAL 9010	24 BRONZE	25 RUST	30 ANTHRACIT E	35 SLATE GREY	40 GREY RAL 9006

ACCESSORIES

	E.TRA.580 Ultra compact type 2+3 hard wired surge protector L 37 x W 30 x H 30
---	--