



Pong 1500

Product code


POG15ANR048CWOD



Features

IP rating	IP66/67
Source type	Mid power LED
LED number	294
CRI	80
Step McAdam	3
Source life time	>110.000h L70 B10 at 25°C ambient temperature
Source flux	3040 lm
Source efficiency	126,7 lm/W
Delivered flux	1735 lm
Delivered efficiency	72,3 lm/W
Input power	24W
Voltage	48 VDC
Insulation class	insulation class III
Power supply	Power supply remote, constant voltage
Management interface	on/off, optional dimming (via accessories)
Light colour/CCT	5000K
Beam angle	120°
Mounting	surface
Finishing	silver anodized
Net weight	1,65kg

Technical drawing



Temperature limits

Working temperature	from -30°C to +55°C
Storage temperature	from -50°C to +80°C

Construction

extruded aluminum alloy, polyurethane resin and plastic cover

Light control

Control and dimming by means of constant voltage control accessories


Connection

Through-wiring, power supply cable length 0,15m with IP68 4-poles connectors

Protections

reverse polarity

Specifications




Dimensions

A	25mm	B	23mm
C	1500mm		

Photometry

120°



5000K	0.2 m	15,5 Klux
619,91 cd	0.5 m	2,5 Klux
1,73 Klm	1 m	620 lux
24	2 m	155 lux
	5 m	25 lux


Lighting effects



Pong 1500

Product code

POG15ANR048CWOD

Client**Project name****Order #****Type****Qty****Technical drawing****Dimensions**

A	25mm	B	23mm
C	1500mm		